

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/EP04/014484

International filing date: 20 December 2004 (20.12.2004)

Document type: Certified copy of priority document

Document details: Country/Office: GB  
Number: 0329849.4  
Filing date: 23 December 2003 (23.12.2003)

Date of receipt at the International Bureau: 07 February 2005 (07.02.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

# PATENT COOPERATION TREATY

REC'D 07 FEB 2005

PCT  
WIPO

PCT

From the RECEIVING OFFICE

To:



The International Bureau of WIPO  
34, chemin des Colombettes  
1211, Geneva 20  
Suisse



The International Searching Authority

NOTIFICATION CONCERNING  
DOCUMENTS TRANSMITTED

Date of mailing  
(day/month/year)

04 FEB 2005

International application No.

PCT/EP2004/014484

The receiving Office transmits herewith the following documents:

1. ☐ the record copy (Article 12(1)) (only for the IB).
2. ☐ the search copy of form PCT/RO/101 (Article 12(1)) (only for the ISA).
3. ☐ the confirmation copy (Administrative Instructions, Section 331) (only for the IB).
4. ☐ substitute sheets (Administrative Instructions, Section 325(a)).
5. ☐ later submitted sheets (Administrative Instructions, Section 309(b)(iii), (c)(ii)).
6. ☐ later submitted drawings (Administrative Instructions, Section 310(c)(iii), (d)(ii)).
7. other document(s):
  - ☐ letter(s) dated: \_\_\_\_\_
  - ☐ \_\_\_\_\_ power(s) of attorney (only for the IB).
  - ☐ statement(s) explaining lack of signature considered to be satisfactory by this receiving Office (only for the IB).
  - ☒ 1 priority document(s) (only for the IB).
  - ☐ fee calculation sheet (only for the IB).
  - ☐ document(s) concerning deposited biological material.
  - ☐ nucleotide and/or amino acid sequence listing(s) in computer readable form (only for the ISA).
  - ☐ PCT EASY diskette (only for the IB).
  - ☐ earlier search(es) (only for the ISA).
  - ☐ Form PCT/RO/106.
  - ☐ Form PCT/RO/ \_\_\_\_\_
  - ☐ \_\_\_\_\_
  - ☐ \_\_\_\_\_

Name and mailing address of the Receiving Office



European Patent Office, P.B. 5818 Patentlaan 2  
NL-2280 HV Rijswijk  
Tel. (+31-70) 340-2040  
Fax: (+31-70) 340-3016

Authorized officer

AA Annik Appelen  
+31 (0)70 340 4846





INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ


EP/04/14484

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

*W. Evans*

Dated

6 January 2005






24DEC03 EB61828-1 000571  
POL/7700 0.00-0329849.4 CHEQUE

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference

PJS/P9737GB

2. Patent application number

(The Patent Office will fill this part in)

0329849.4

3. Full name, address and postcode of the or of each applicant (underline all surnames)

PreciSense A/S  
Dr. Neergaards Vej 3  
DK-2970 Horsholm  
Denmark

Patents ADP number (if you know it)

8773525001

If the applicant is a corporate body, give the country/state of its incorporation

Denmark

4. Title of the invention

Fluorometers

5. Name of your agent (if you have one)

W. H. Beck, Greener & Co.

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

W. H. Beck, Greener & Co.  
7 Stone Buildings  
Lincoln's Inn  
London WC2A 3SZ

Patents ADP number (if you know it)

323001

6. Priority: Complete this section if you are declaring priority from one or more earlier patent applications, filed in the last 12 months.

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. Divisionals, etc: Complete this section only if this application is a divisional application or resulted from an entitlement dispute (see note f)

Number of earlier UK application

Date of filing  
(day / month / year)

8. Is a Patents Form 7/77 (Statement of inventorship and of right to grant of a patent) required in support of this request?

Answer YES if:

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

Yes

Otherwise answer NO (See note d)

Patents Form 1/77

9. Accompanying documents: A patent application must include a description of the invention. Not counting duplicates, please enter the number of pages of each item accompanying this form:

Continuation sheets of this form

Description	11
Claim(s)	3
Abstract	
Drawing(s)	10 10 10

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for a preliminary examination and search (Patents Form 9/77)

Request for a substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature(s)

*Peter J. Smart*

Date 23.12.03

12. Name, daytime telephone number and e-mail address, if any, of person to contact in the United Kingdom

Mr Peter J. Smart - (020) 7693 5600

**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

**Notes**

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered YES in part 8, a Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- Part 7 should only be completed when a divisional application is being made under section 15(4), or when an application is being made under section 8(3), 12(6) or 37(4) following an entitlement dispute. By completing part 7 you are requesting that this application takes the same filing date as an earlier UK application. If you want the new application to have the same priority date(s) as the earlier UK application, you should also complete part 6 with the priority details.

Fluorometers

The present invention relates to fluorometers, being apparatus for producing and measuring fluorescence, whether  
5 using intensity or time resolved measurements.

Epifluorescence microscopes conventionally have a linear optical arrangement in which a sample location, beam splitter and detector are arranged spaced, for instance vertically, along a common axis in a first direction, with an excitation  
10 light source off to one side. This arrangement dictates a minimum height constraint so as to provide room for fluorescence light emitted from a sample location to be collimated by a lens system, passed through the beam splitter, filtered to remove wavelengths other than that of  
15 the fluorescence and finally to be focussed onto the detector. Such a conventional arrangement is illustrated in Figure 1 as discussed in greater detail below. In fluorescence applications the intensity of the emitted fluorescence is usually weak. Furthermore, the fluorescence  
20 is emitted isotropically or according to a Lambertian radiation pattern if the fluorophore is situated in a light scattering medium such as skin. In both cases the detected fluorescence increases with the numerical aperture of the optical system. In the common epifluorescence set-up a large  
25 numerical aperture is normally obtained by the use of a number of lenses, which introduces reflection loss and light scattering even for coated lenses.

It would be desirable to develop an alternative general  
30 optical arrangement with reduced complexity that can be used to reduce the necessary height of the apparatus measured from a sample location.

Accordingly, the present invention now provides in a first aspect apparatus for the production and detection of fluorescence at or below a surface, said apparatus comprising:

5 a light source for directing fluorescence excitation light along a light path extending over a said surface;

10 a reflector having a three dimensionally curved, shell-like light reflecting interface positioned to receive light from the light source passing over said surface along a portion of said light path and to reflect said light transversely with respect to said portion of the light path so as to focus said light on an illumination zone at or below said surface for stimulation of  
15 fluorescence at said zone, and to collect fluorescence light emitted at said zone and to reflect and at least partially collimate said light to pass back along said portion of the light path; and

20 a detector for receiving said light emitted as fluorescence after reflection at said interface.

The 'surface' referred to above may be a physical surface defined by an interface between two different  
25 materials or may be a virtual surface definable with respect to the apparatus.

The apparatus may further comprise a beam splitter reflecting light emitted by said light source to pass to said  
30 reflector and receiving fluorescence light from said reflector and passing said fluorescence light to said detector.

Said reflector, light source and detector are preferably arranged in a generally coplanar manner and said beam splitter preferably has a planar reflective interface that lies in a plane orthogonal to the co-planarity of the reflector, light source and detector.

The apparatus may further comprise an excitation filter selecting an excitation wavelength from the light emitted by the light source to pass to said reflector.

The apparatus may further comprise an emission filter selecting an emitted fluorescence wavelength to pass to said detector.

The apparatus may comprise a lens focussing fluorescence light on said detector. Alternatively, a further focussing reflective interface may be used.

The or each said reflector interface may substantially have the form of a partial paraboloid, aspheric, toroidal, or biconic surface. Such a reflector interface may be paraboloid, aspheric, toroidal, or biconic surface. Spheric surfaces and aspheric surfaces such as hyperbolas, parabolas, ellipsoids and oblate ellipsoid reflector interfaces may be defined by an equation

$$Z = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}}$$

wherein:

c is from 0.07 to 0.5 and k is from -1.5 to -0.7, where z is the "sag" of z-coordinate along the rotational axis, c is the curvature (the reciprocal of the radius R), k is the conical constant and r is the radial coordinate. Other surfaces may be described by similar equations involving an added Taylor expansion. Similarly, equations are available for toroids,

e.g. faceted toroids, or piecewise linear toroids and for biconic surfaces..

The reflector interface of the reflector directing light to the illumination zone may include that part of a  
5 paraboloid, aspheric, toroidal, or biconic surface that is generated by the cutting of a paraboloid, aspheric, toroidal, or biconic surface by a right circular cylinder erected centred on the illumination zone.

Said reflector interface may preferably substantially  
10 have the form of a part of a half paraboloid.

The apparatus may further include a housing containing the light source, reflector and detector and having a base surface containing a window for passing excitation light out of the housing and receiving fluorescence light into the  
15 housing and being for engagement in use against the said surface at or below which said fluorescence occurs.

Preferably, said light path makes an angle of no more than 10 degrees with a plane defined by said base surface.

The invention will be further described and illustrated  
20 with reference to the accompanying drawings in which:

Figure 1 is a schematic side elevation view of a conventional epifluorescence measuring apparatus;

Figure 2 is a perspective view of a first embodiment of apparatus according to the present invention;

25 Figure 3 is an illustration showing the zone of a parabolic mirror in which most energy is collected when light is emitted from a surface over which the mirror lies;

Figure 4 is a plan view from above of a second embodiment according to the invention;

30 Figure 5 is a perspective view of the apparatus of Figure 4;

Figure 6 is a cross section on the line VI-VI' marked in Figure 4;

Figure 7 shows a modification of the apparatus of Figure 4;

5 Figure 8 shows a third embodiment according to the invention in plan from above;

Figure 9 is a graph of the variation in shape of a parabolic mirror with the conical constant; and

10 Figure 10 is a graph showing the variation in the ratio of detected optical power and illumination power with changing conical constant.

A common set up for epifluorescence measurement is shown in Figure 1. It is designed for producing and detecting fluorescence at a sample location 10, which might be for  
15 instance at or below the surface of a body or article, e.g. on a microscope slide. Typically such a surface will be horizontal and for convenience, this is assumed in the following description of the apparatus. An excitation light source 12, such as an LED, is positioned off to one side of  
20 the sample location 10 and at a height  $h$  above the sample location. The LED emits excitation light 16 which is passed through an excitation filter 14 to select a desired excitation wavelength. The excitation light falls on an angled beam splitter 18 such as a parallel sided dichroic  
25 beam splitter 18. A portion of the excitation light is reflected down at right angles towards the sample location and passes through a focussing lens system 20 comprising one or more simple or compound lenses.

Fluorescence and reflected excitation light emanating  
30 from the sample location are captured by the lens system 20 and collimated into a parallel beam which passes through the beam splitter 18 to an emission filter 22, which ideally

removes all but the fluorescence wavelength, and from there to a second lens system 24 that focuses the fluorescence onto a detector 26. Like the lens system 20, the lens system 24 may comprise one or more simple or compound lenses.

5 The whole device has a total height above the sample of  $h'$ , which is around  $3 \times h$ .

It has been proposed to monitor concentrations of chemical species in the human or animal body by fluorescence based techniques. These would involve directing the  
10 excitation light onto the skin and detecting fluorescence emission from the skin. Relevant teachings include WO00/02048 and WO02/30275.

We have noted that it would be desirable in such circumstances and others to reduce the dimension  $h'$  of the  
15 fluorescence detection apparatus used.

Figures 2 shows an embodiment of apparatus according to the invention. Here, the apparatus is depicted placed on the surface of the skin or a similar surface on which  
fluorescence is to be detected. For convenience in the  
20 following description, the plane of the skin will be treated as being horizontal. A light source 32 emits light along a path parallel to the skin surface, and determines a height  $h$  for the apparatus which approximately equals to the total height  $h'$  of the device.

25 The light passes through an excitation filter 34 to a dichroic beam splitter 38 disposed in a vertical plane and is diverted towards a half paraboloid shaped mirror reflector 40 which replaces the lens system 20 of the conventional apparatus. The reflector focuses the light down onto an  
30 illumination zone 30 on the skin surface or towards an illumination zone just below the skin surface. The reflector collects and collimates fluorescence emissions from the

illumination zone and directs the emitted light back to the beam splitter, which it passes through to reach an emission filter 42. From there, the light is focused by a lens system 44 of the same type as lens system 24 and is detected at a  
5 detector 46..

It can be seen that the vertical height of the apparatus has been reduced from approximately  $3 \times h$  in Figure 1 to just  $h$  in Figure 2.

Generally, interference filters are used in fluorometers  
10 as the excitation and emission filters. These require that the incident light be orthogonal to the plane of the filter if the expected wavelength passing properties are to be obtained, because with obliquely incident light, the filter pass band will be shifted towards shorter wavelengths.  
15 Collimation of the light beams incident on these filters is therefore required.

The paraboloid reflector 40 may be constructed in a number of ways to produce a reflecting interface of the desired shape. For instance, the interface may be between  
20 air inside the paraboloid and a reflective concave interior surface of a body. Alternatively, the interface may be formed at the convex exterior surface of a solid hemi-paraboloid member, for instance a silvered exterior of a glass or plastics hemi-paraboloid block.

25 The whole of the illustrated apparatus will be bounded by a housing or casing (as seen in Figure 6) having a bottom face containing an aperture which may be filled with a transparent window (suitably of glass, silica or in some applications plastics) for protecting the optics against dust  
30 and humidity and for allowing the passage of excitation and fluorescence light to and from a sample in the illumination

zone. Said apparatus may thus be a simple opening in the casing or an optical window.

Signals from the detector may be fed to suitable electronic circuitry for analysis in a known manner. The LED  
5 may be powered by suitable electronic circuitry as known and the LED supply circuitry and the detected signal processing circuitry will generally form part of an integral circuitry for producing intensity based or time resolved (frequency domain) measurements of the fluorescence, e.g. in a FRET  
10 (fluorescence resonance energy transfer) based assay.

The illustrated apparatus provides a high numerical aperture for the capture of fluorescence from the illumination zone whilst enabling a compact optical geometry suited for use where space is at a premium, e.g. in a device  
15 to be worn on the body.

Not all of the illustrated paraboloid surface is needed in order to obtain good results. The paraboloid need not, as shown, be arranged with its axis coincident with the surface on which the device is to be used but may be angled up to  
20 gain some additional height above the surface for the detector optics. The beam of fluorescent light may not be collimated entirely by the reflector but may in part be collimated by an auxiliary lens system. The physical illumination zone of the apparatus need not lie at the focus  
25 of the reflector. The reflector interface need not be in the form of a true paraboloid. These concepts are further illustrated in subsequent Figures.

As shown in Figure 3, the area of the paraboloid surface M that will receive and collimate out to the detector most of  
30 the fluorescence emitted from the illumination zone will be that defined by the intersection of a right circular cylinder C centred on the illumination zone with the paraboloid

surface itself. The remainder of the paraboloid surface need not therefore be present. Clearly, the smaller the cylinder, the less light will be captured, so preferably at least as much of the paraboloid is present as is defined by the intersection with a cylinder of a radius  $r$  not less than 50%, preferably not less than 75%, more preferably not less than 90% of the distance marked  $f$  from the origin to the focal point of the paraboloid. The radius  $r$  of the cylinder need not be smaller than the focal length of the parabolic mirror, as in the case shown in Figure 3, but can be larger.

Whilst in Figure 2 a lens system is shown focusing the light onto the detector, it will be appreciated that this could also be a reflector system instead, which might suitably resemble that used to focus the excitation light on the illumination zone. Such a system is shown in Figures 4 to 6.

In the illustrated apparatus, the illustrated components are as in Figure 2 except that the lens system 44 is replaced by a part parabolic mirror 45 which resembles mirror 40 but is arranged to focus the fluorescence light to the side where the detector 46 is now positioned. As seen in Figure 6, the apparatus comprises a housing 50 having a base plate 52 lying on the skin and containing a window 54 as previously described which defines the illumination zone 30. The housing comprises upper and lower half shells having internal formations to cradle and support the optical components, the shells being secured together by screws as shown.

As shown in Figure 7, the base surface of the housing may lie at an angle  $\alpha$ , preferably not exceeding  $10^\circ$ , more preferably not exceeding  $5^\circ$ , to the axis of the paraboloid surface. This will give some additional space for the optical and electronic components but will also result in

some additional height at the detector end of the apparatus. This modification may be employed both in relation to the embodiment using mirrors at each end as shown and in relation to the embodiment of Figure 2. Furthermore, the focal point of the mirror 40 may differ from the location of the sample, as shown on Figure 7 by the distance  $\delta$ , in order to compensate for the radiation pattern and scattering properties of the sample or surrounding media as in the case of detecting fluorescence under the skin.

As shown on Figure 8, an auxiliary lens system comprising one or more simple or compound lenses 41 positioned in front of mirror 40 may be used to produce further collimation.

Similarly, the shape of the reflector may deviate from that of a paraboloid in order to accommodate to the radiation pattern and scattering properties of the sample or surrounding media as in the case of detecting fluorescence under the skin. If this leads to an incomplete collimation of the fluorescence emissions, further collimation may be carried out using an auxiliary lens system 41 as illustrated.

Alternative curved surfaces that may be used include toroidal, aspheric and biconic surfaces.

For an aspheric surface defined by

$$Z = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}}$$

c is preferably within the range of 0.07 to 0.5 and k is preferably within the range of -1.5 to -0.7, where z is the "sag" of z-coordinate along the rotational axis, c is the curvature (the reciprocal of the radius R) and k is the conical constant and r is the radial coordinate. The shape of the

mirror is shown in Figure 9 for various values of the conical constant.

In Figure 10 the influence of the conical constant on the detected optical power is shown.

5       The illumination zone need not be a point or a circular area but by the effect of the use of non-paraboloid reflector shapes may be elongated either transversely or longitudinally of the axis of the reflector.

10       In this specification, unless expressly otherwise indicated, the word 'or' is used in the sense of an operator that returns a true value when either or both of the stated conditions is met, as opposed to the operator 'exclusive or' which requires that only one of the conditions is met. The word 'comprising' is used in the sense of 'including' rather  
15       than in to mean 'consisting of'.

## CLAIMS

1. Apparatus for the production and detection of  
fluorescence at or below a surface, said apparatus  
comprising:
- a light source for directing fluorescence excitation  
light along a light path extending over a said surface;
- a reflector having a three dimensionally curved, shell-  
like light reflecting interface positioned to receive  
light from the light source passing over said surface  
along a portion of said light path and to reflect said  
light transversely with respect to said portion of the  
light path so as to focus said light on an illumination  
zone at or below said surface for stimulation of  
fluorescence at said zone, and to collect fluorescence  
light emitted at said zone and to reflect and at least  
partially collimate said light to pass back along said  
portion of the light path; and
- a detector for receiving said light emitted as  
fluorescence after reflection at said interface.
2. Apparatus as claimed in Claim 1, further comprising a  
beam splitter reflecting light emitted by said light  
source to pass to said reflector and receiving  
fluorescence light from said reflector and passing said  
fluorescence light to said detector.
3. Apparatus as claimed in Claim 2, wherein said  
reflector, light source and detector are arranged in a

generally coplanar manner and said beam splitter has a planar reflective interface that lies in a plane orthogonal to the co-planarity of the reflector, light source and detector.

5

4. Apparatus as claimed in any preceding claim, further comprising an excitation filter selecting an excitation wavelength from the light emitted by the light source to pass to said reflector.

10

5. Apparatus as claimed in any preceding claim, further comprising an emission filter selecting an emitted fluorescence wavelength to pass to said detector.

15

6. Apparatus as claimed in any preceding claim, comprising a lens or a second reflector focussing fluorescence light on said detector.

20

7. Apparatus as claimed in any preceding claim, wherein said reflector interface substantially has the form of a partial paraboloid, aspheric, toroidal, or biconic surface.

25

8. Apparatus as claimed in Claim 7, wherein said reflector interface is defined by an equation

$$Z = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}}$$

wherein:


c is from 0.07 to 0.5 and k is from -1.5 to -0.7, where z is the "sag" of z-coordinate along the rotational axis, c is the curvature (the reciprocal of the radius

30

R),  $k$  is the conical constant and  $r$  is the radial coordinate.

- 5 9. Apparatus as claimed in Claim 7 or Claim 8, wherein said reflector interface includes that part of a paraboloid, aspheric, toroidal, or biconic surface that is generated by the cutting of a paraboloid, aspheric, toroidal, or biconic surface by a right circular cylinder erected centred on the illumination zone.
- 10 10. Apparatus as claimed in Claim 7 or Claim 8, wherein said reflector interface substantially has the form of a part of a half paraboloid.
- 15 11. Apparatus as claimed in any preceding claim, further including a housing containing the light source, reflector and detector and having a base surface containing a window for passing excitation light out of the housing and receiving fluorescence light into the housing and being for engagement in use against the said surface at or below which said fluorescence occurs.
- 20 12. Apparatus as claimed in any preceding claim, wherein said light path makes an angle of no more than 10 degrees with a plane defined by said base surface.
- 25

Fig 1









Fig 2










Fig 4






Fig 5






Fig 6






Fig 7






Fig 8






Fig 9






Fig 10

